

Telehandler / Zoom Boom

Used Telehandler Minnesota - Telehandlers have numerous names including a teleporter, Cherry picker, telescopic handler or boom lift. This industrial equipment is commonly used in a variety of industries including agriculture. It is similar to a forklift and a crane as it has a boom, enabling it to extend upwards and forwards from the vehicle. Numerous attachments can be placed at the end of the articulating boom to conduct a variety of different jobs. Common attachments include pallet forks, a winch, a bucket or a muck grab. The pallet forks are the most popular telehandler attachment. Pallet forks enable the operator to move loads to and from a variety of locations that would otherwise be considered unreachable with a standard forklift. Telehandlers allow cargo pallets to be transported from trailers and placed on racking, rooftops or other difficult to reach locations. Normally, high rooftop applications would require the use of a crane; however, telehandlers can complete this task more efficiently. Of course, it isn't always affordable or practical to use secondary equipment or a crane to complete certain tasks. A bucket grab or a bucket is the most common attachments for telehandlers within the agricultural sector. Moving items from unreachable locations that cannot be completed with a backhoe loader or wheeled loader give telehandlers a huge advantage. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Relying on one piece of equipment to complete a variety of jobs saves time, money and storage. Telehandler machines can work in conjunction with a crane jib. Many attachments can be used such as power booms, grain and dirt buckets and rotators. The agricultural models can use three-point linkage and power take-off to make telehandlers multi-tasking. However, the main advantage of the telehandler is additionally its' largest limitation. The boom acts as a lever when it extends or raises with heavy loads. Even with rear counterweights, this machine may become unstable from time to time; decreasing the lift capacity when the distance between the center of the load and the front of the wheels or the working radius increases. If the machine works as a single boom loader instead of using twin arms while carrying a large load, there is a chance that weakness can occur even in the most carefully designed units. A 5000 lb. capacity telehandler could lift 400 lbs. safely while fully extended with a retracted boom in conjunction with a low boom angle. Raising the same piece of equipment 70 degrees could allow this machine with a five thousand pound lift capability and retracted boom to support up to ten thousand pounds. Monitoring the angle, weight and boom height, there are load charts on this equipment to outline which tasks can be safely conducted. Updated telehandler models have computers and sensors. When the telehandler limits have been surpassed, the operator is cut off and warned from supplying further control input. The lifting capacity is enhanced by front stabilizers that maximize the lifting capacity from a stationary position. A mobile crane can also use a bucket is another option consisting of a stabilized rotary joint found between upper and lower frames. There are many models of telehandlers differing in size, weight, boom designs and reach. If the machine weighs in at eleven thousand pounds or less, it can be part of the compact category. Compact units have a two-stage boom compared to larger machines that feature three or four boom designs. A low pivot boom ensures better operator visibility for transporting loads on compact units. There are narrower and smaller dimensions offered with the compact telehandler. The compact units offer a reach capacity between thirteen to twenty feet and a lifting capacity ranging from five thousand to seven thousand pounds. These versatile machines make the compact telehandler extremely popular. Telehandlers can function as a pick and place unit or a tool carrier. This machine is often used in locations that are cramped and tight. It is common for contractors to use this machine during framing and for residential jobs where there are height restrictions. Telehandlers can enter internal building access in hard-to-reach locations. Compact telehandlers are commonly used in nurseries, landscaping, multi-story construction, building strip malls and garages, masonry, erecting steel and more. Agri-business and farming applications rely on telehandlers for a variety of jobs. Telehandlers are

made with two or four-wheel drive as well as crab steering. This machine can traverse longer distances with two-wheel drive at higher speeds to facilitate easy travel between worksites. The 4-WD units are capable of having a tighter turning radius and can travel difficult terrain. Crab steering enhances the units' maneuverability while allowing each set of wheels to move forty-five degrees to the right or left. Compact telehandlers have numerous cab environments to choose from. On entry-level models, there is a rollover cage for added safety. Newer units come with windshield wipers, a defroster, a heater and a totally enclosed cab. All compact telehandler cabs are spacious to accommodate the operator as comfortable as possible. Extra amenities including air conditioning, satellite radio, suspension seats, tilt steering and cup holders are available. Many high-pressure hydraulics and high-flow auxiliary hydraulics operate the numerous attachments. The different attachments allow the machine to be capable of many options. All of these attachments enable the machine to conduct a variety of jobs. Ground engaging work is often completed by compact units. Adding a bucket attachment can make a compact telehandler transform into a mini excavator. There are popular attachments including brooms for sweeping, truss booms for extended reach, side-shifting and rotating fork carriages, heavy and light-duty buckets, augers for planting trees or digging holes and many items. Skid steer attachments are being made for versatility and other compact telehandler designs.